



SALIENT FEATURES

- IGBT based double conversion on-line Topology
- DSP/Microprocessor Controlled
- Wide Input Range
- LCD Display
- Charger for extended backup time
- Scalable Battery option
- Generator Compatible

CERTIFICATION

- RoHS
- OHSAS 18001
- ISO 9001
- ISO 14001

Address : 66 Salkia School Road, 'AAVAS', B Block, Howrah - 711 106

Phone : 8420007562

E-Mail : service@epochelectronica.com

TECHNICAL SPECIFICATIONS FOR EPOCH 1000VA LINE-INTERACTIVE UPS

MODEL	EPOCH 1000 L.I.
Capacity	1000VA
INPUT	
Voltage	145Vac-280Vac
Frequency	50Hz $\pm$ 5%
OUTPUT	
Voltage Auto Sensing	230 Vac $\pm$ 10%
Transfer Time	Below 10 milliseconds
Wave Form (Battery Mode)	Simulated Sine wave
BATTERY	
Type	Sealed, maintenance-free lead acid
Capacity	12V/7AH/2nos (in built batteries).
INDICATOR	
AC Mode	Green lighting
Battery Mode	Green flashing every 10 sec.
ENVIRONMENT	
Humidity	0-90%
Operating Temperature	0-40°C (non condensing)
PHYSICAL DIMENSION	
Weight	8.0 Kgs
Size (wxdxh)mm	146 mm x 350 mm x 160 mm

Address : 66 Salkia School Road, 'AAVAS', B Block, Howrah - 711 106

Phone : 8420007562

E-Mail : service@epochelectronica.com